



DURALINER™ POND LINING

45 MIL EPDM RUBBER LINER

The preferred choice of professional landscapers, nurseries, koi pond and water garden installers!

- Easy to shape and form! Stays flexible even in extreme temperatures from -40° to 175°F.
- Durable rubber is weather and UV resistant - will not crack with age
- Puncture resistant
- Fish and plant friendly



BOXED LINER

Part #	Boxed Liner Size	Weight per Box	Boxes per Pallet/ Pallet Ship Weight*	UPC/GTIN
BPL810	8' x 10'	29 lbs.	60 boxes / 1,900 lbs.	00850045556716
BPL1010	10' x 10'	35 lbs.	45 boxes / 1,725 lbs.	00850045556723
BPL1015	10' x 15'	52 lbs.	24 boxes / 1,400 lbs.	00850045556730
BPL1515	15' x 15'	77 lbs.	24 boxes / 2,000 lbs.	00850045556747
BPL1520	15' x 20'	102 lbs.	18 boxes / 1,990 lbs.	00850045556754
BPL1525	15' x 25'	129 lbs.	18 boxes / 2,475 lbs.	00850045556761
BPL2020	20' x 20'	136 lbs.	18 boxes / 2,600 lbs.	00850045556778

* Approximate pallet weight based on 150 lb. pallet

CUT LINER

Get the right size pond liner for the job. Available in standard widths and cut to your desired length, custom cut liner can save you money in installation time, reduce waste and help prevent leaks that may occur when liner is seamed in the field.

Weight is 330 lbs./1,000 sq. ft.

Standard widths: 5', 10', 15', 20', 25', 30', 35', 40', 50'



- Available in many pre-cut sizes, custom cut for your pond, and by the roll at various widths and lengths for larger ponds
- **20 year limited warranty**



ROLLS - 50'

Part #	Rolled Liner Size	Core Length	Approx. Ship Weight	UPC/GTIN
RPL105	10' x 50'	7'	185 lbs.	00850045556792
RPL155	15' x 50'	7'	265 lbs.	00850045556808
RPL205	20' x 50'	7'	350 lbs.	00850045556815
RPL255	25' x 50'	7'	430 lbs.	00850045556822
RPL305	30' x 50'	7'	510 lbs.	00850045556839
RPL355	35' x 50'	11'	600 lbs.	00850045556846
RPL405	40' x 50'	11'	685 lbs.	00850045556853
RPL505	50' x 50'	11'	850 lbs.	00850045556860

ROLLS - 100'

Part #	Rolled Liner Size	Core Length	Approx. Ship Weight	UPC/GTIN
RPL051	5' x 100'	7'	185 lbs.	00850045556877
RPL101	10' x 100'	7'	350 lbs.	00850045556884
RPL151	15' x 100'	7'	510 lbs.	00850045556891
RPL201	20' x 100'	7'	675 lbs.	00850045556907
RPL251	25' x 100'	11'	850 lbs.	00850045556914
RPL301	30' x 100'	11'	1,010 lbs.	00850045556921
RPL351	35' x 100'	11'	1,175 lbs.	00850045556938
RPL401	40' x 100'	11'	1,335 lbs.	00850045556945
RPL501	50' x 100'	11'	1,660 lbs.	00850045556952

45 MIL EPDM RUBBER LINER

DURALINER™

TECHNICAL SPECIFICATIONS

Physical Property	Test Method	Requirement of ASTM D 7465 (Type 1)	EasyPro DuraLiner™ Values
Color	-	-	Black
Thickness (mil)	ASTM D-412	45 mil	45 mil
Tensile Strength (MPa)	ASTM D-412	9 Min	9.1
Elongation Ultimate (%)	ASTM D-412	300% Min	350%
Angular Tear (kN/m)	ASTM D-624	26.27 Min	27
Tensile Set (%)	ASTM D-412	10% Max	7%
Brittleness Point Max °F (°C)	ASTM D-2137	-49°F (-45°C)	No Cracks
Ozone Resistance	ASTM D-1149	No Cracks	No Cracks/PASS
Heat Aged* Tensile Strength (MPa)	ASTM D-412	8.30 Min	9.0
Heat Aged* Elongation Ultimate (%)	ASTM D-412	200% Min	275%
Heat Aged* Angular Tear (kN/m)	ASTM D-624	21.9 Min	23.90
Linear Dimension Change (%)	ASTM D-1204	±1	-0.45%
Water Absorption 166 hours @ 70°F (21°C) (%)	ASTM D-471	+8,-2	+1.7%
Visual Inspection	ASTM G-151 ASTM G-155	PASS	PASS

The above values for DuraLiner™ were taken from specimens made under reproducible conditions, however, they may differ somewhat on actual production/supply due to vulcanization conditions at the factory.

The information given herein is based on tests conducted in an in-house laboratory and/or independent accredited laboratories. While the information is presented as true and accurate to the best of our knowledge, EasyPro Pond Products® assumes no responsibility or liability regarding the use of this information. The right to make periodic revisions of the specifications without prior notice is reserved. Many factors beyond our control can affect and influence the use and performance of our products in any application. Since these factors are uniquely with the users' knowledge and control, it is essential that users evaluate the product to determine its suitability for the purpose.

*Heat aged test conducted for 670 hours at 240°

EPDM ACCESSORIES

Liner Underlayment A non-woven geotextile fabric used as an underlayment to protect the rubber liner from tree roots, rocks, and other sharp objects.

Seam Tape Kit Used for seaming two panels of EPDM liner together. Contains EPDM seam primer and EPDM seam tape, seam roller, wipes and two primer application pads.

Other EPDM Accessories Adhesive, lap sealant, pipe flashings, air vents and more are available for unique applications.

